



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: BP192V557C-16K

External battery pack for use with select Tripp Lite UPS Systems

Highlights

- Extends runtime of compatible Tripp Lite UPS Systems using 192VDC configuration
- Includes built in 7A charger
- Includes UPS connection cabling
- Hardwire installation
- 10 year design life
- 1-year warranty

Description

Tripp Lite's BP192V557C-16K External Battery Pack with built-in 7A charger offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes heavy gauge cabling to connect to host UPS. Multiple BP192V557C-16K batteries can be daisy-chained for longer runtime configurations with appropriate contractor-supplied battery pack interconnection cabling (see manual). Internal battery charger is powered via hardwire connection to 120V 30A electrical service.

COMPATIBLE UPS SYSTEMS: SU16000RT4U, SU16000RT4UHW and other Tripp Lite UPS systems specifying the use of this battery pack

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- 10 year design life
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- Cabling to connect one BP192V557C-16K to host UPS is included - cabling for additional battery packs is contractor supplied
- Includes built-in 7A charger powered via hardwire 120VAC 30A input connection
- 1 year warranty

Specifications

BATTERY	
Expandable battery runtime	Multiple battery packs can be daisy-chained to the UPS for extended runtime. Configuration specific cabling for multi-battery pack configurations is contractor provided.
Connects to UPS via	Included cabling enables connection between unique UPS connector and hardwire DC terminals in battery pack. Cabling to connect multiple external battery packs is contractor provided
DC system voltage	192VDC
PHYSICAL	
Shipping weight (lbs)	1200
Shipping weight (kg)	544.8
Shipping Dimensions (HWD/in)	63 x 37 x 36

Shipping Dimensions (HWD/cm)	160 x 94 x 91.4
Unit weight (lbs)	1130
Unit weight (kg)	513
Unit Dimensions (HWD/in)	60 x 32.4 x 28.8
Unit Dimensions (HWD/cm)	152.4 x 82.3 x 73.2
Material of construction	Steel
Form factors supported	Tower

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4083.